Excel in Your Field

Specifications

CATEGORY	XR4140	XR4140C	XR4145	XR4145C	XR4150	XR4150C	XR4155	XR4155C	
CATEUUNT	XR4140H	XR4140HC	XR4145H	XR4145HC	XR4150H	XR4150HC	XR4155H	XR4155HC	
ENGINE									
Туре		3Cyl. In-	line Vertica	al, Water-co	oled 4cycle	Turbo Diese	el, CRDI		
Model(Tier4)	L3C19-T								
Engine HP(Gross)	40		45		50		55		
PTO HP	34.4		38.7		43.0		47.3		
	32	32.0		36.0		40.0		44.0	
Rated speed, rpm	2,600								
Displacement-cu, in ³ .	114.7								
Fuel tank capacity, gal	12.4 (CABIN) / 10.6 (ROPS)								
Alternator(V-A)	12-70								
DRIVE TRAIN									
Transmission	Synchro shuttle / HST								
No. of Speed	F16 x R16 (GEAR) / 3 Ranges (HST)								
Brakes	Wet, Multi - disc								
Steering	Hydrostatic Power Steering								
PTO									
Туре	Independent								
Rear, rpm	540								
Mid PTO(Option)	2,000								
HYDRAULIC SYSTEM									
Control system	Position / Draft								
Main pump, gpm	8.2								
Steering pump, gpm	4.1 (GEAR) / 5.5 (HST)								
Total flow, gpm	12.3 (GEAR) / 13.7 (HST)								
Category, 3pt hitch	CAT I CAT II								
Hitch Lift capacity, lbs(Hitch end)	2,755								
Remote valves	2 pairs								
DIMENSION									
Overall length, Bumper to link in.	133								
Overall width with tires, in.	62.5								
Wheelbase, in.	73.2								
Ht to top of rops, in.	93	92	93	92	93	92	93	92	
TIRE SIZE									
Ag Front / Rear	9.5 - 16 / 13.6 - 24								
IND Front / Rear	12 - 16.5, 17.5L - 24								
Turf Front / Rear		28 x 8.5 - 15 / 41 x 14 - 20							
WEIGHT									
Total weight without ballast, lbs.	3,869	4,380	3,869	4,380	3,869	4,380	3,869	4,380	
	3,935	4,446	3,935	4,446	3,935	4,446	3,935	4,446	

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- · Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- · Instrumentation-alternator
- Warning and engine oil pressure light
- Remote control vales (2 pairs)
- Hydrostatic power steering
- · Front loader valve and joystick
- Hydraulic draft and position control
- · Extendable lower links and telescopic stabilizers
 - Drawbar
- Turn signals
 - · Safety flasher



(956) 318-1370 • (956) 605-0051

info@rockinmoose.com 3901 W. Hwy 107 - McAllen, TX

Front end Loader LL4104 Tractor Application XR4100 Series Bucker Size, in. 72 Maximum Lift height, in. 96.3 Clearance with Attachment Dump, in. Reach at Maximum Height, in. 90 Maximum Dump Angle, deg. 65 34 Maximum Rollback Angle, deg. 4.3 Digging Depth, in. Overall Height in Carry Position, in. 49.2 2,713 Lift Capacity(@ Pivot pin), lbs. Breakout Force(@ Pivot pin), lbs. 3.802

Backhoe	LB2105		
Tractor Application	XR4100 Series		
Digging Depth, in.	89.8		
Reach from centerline of swing Pivot, in	125.2		
Loading Height, in.	72.4		
Swing Arc, deg.	180		
Transport Height, in.	83.5		
Bucket Rotating, deg.	180		
Stabilizer Spread(Down position), in.	68.7		
Stabilizer Spread(Up position), in.	46.5		
Bucket Digging force, lbs.	2,673		

Additional Equipment on Cab Models

- Deluxe cabin with Heating and A/C
- · Cabin air recirculation
- · Interior lighting

Dealer Installed Options

- Mid PTO
- Beacon lamp kit
- Deluxe stereo system with CD Player, USB
- · Room mirror
- Rear wiper
- · Sun screen



XR4100 Series

XR4140 / XR4140H / XR4140C / XR4140HC / XR4145 / XR4145H / XR4145C / XR4145HC / XR4150H / XR4150C / XR4150H / XR4150C / XR4150H / XR4155 / XR4155 / XR4155H / XR4155C / XR4155HC | Premium Compacts **Premium Compacts**



- Eco-friendly TIER 4 40 / 45 / 50 / 55HP engines
- 5 year warranty*
- 16F x 16R fully synchronized shuttle shift or 3 range HST with cruise control
- Front wheel mechanical assist 4WD
- Choice of industrial, ag or turf tires at no additional cost
- Available with quick attach skid steer compatible front end loader with grill guard
- Available sub frame mounted, quick attach 7' backhoe
- Optional mid-mount PTO

P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

XR4100 Series Premium Compacts







Hydrostatic transmission models

Maximizes ease of use with effortless, clutchless and instant speed and directional changes with a simple push of the pedals



Flat platform

With rubber mat and side mounted gear lever, maximizes space, improves operator comfort, and makes getting on/off tractor easier



PTO switch

Turn the independent PTO on or off with a simple switch





New LS Tier 4 CRDI Engine

Meets EPA's most stringent emission standards while delivering rated horsepower quietly with low vibration



Provides accessibility for easy maintenance



2 sets of remotes and detent function standard

Adds functionality and improves ease of use by allowing attachment of hydraulically controlled implements without the high, additional costs like others in its class to add the remotes as options



Your choice of tires

Choose ag, industrial, ag or turf tires at no additional cost



Full function dash panel

Important functional data is available at a glance for optimum performance and control



Deluxe adjustable seat with retractable seat belt and arm rests

Keeps you safe and comfortable even during long operations