Excel in Your Field

Specifications

CATEGORY	MT573C	MT573CPS	Front end Loader
ENGINE			Tractor Application
Туре	4 Cylinder, CRDI, Water-cooled		Bucket Size, in.
Model	L4C25-T		Maximum Lift Height, in.
Emission	Tier4 Final		Clearance with Attachment Dump, in.
Engine HP, kW	73 (54.4)		Reach at Maximum Height, in.
PTO, HP	62		Maximum Dump Angle, deg.
Rated speed, rpm	2,500		Maximum Rollback Angle, deg.
Displacement, in ³	152.9		Digging Depth, in.
Fuel tank capacity, gal	26.4		Overall Height in Carry Position, in.
DRIVE TRAIN			Lift Capacity (@ Pivot pin), lbs.
Transmission type (option)	Synchro Shuttle	Power Shuttle	Breakout Force (@ Pivot pin), lbs.
No. of speed	F20	x R20	Approx. Weight (Loader w/o Bucket), lbs.
Forward speed, mph	0.12 ~ 20.6		
РТО			
Туре	Independent		
Rear, rpm	540 / 750 / 1,000		
HYDRAULIC SYSTEM			
Control system	Position / Draft		
Implement pump, gpm	13.2		
Steering pump, gpm	6.6		
Total flow, gpm	19.8		
Category, 3pt hitch	CAT II		
Hitch lift capacity, lbs	6,614		
Remote ports	3 pairs (Front), 3 pairs (Rear)		
DIMENSION			
Overall length, Frame to link, in	150		
Overall width with tires, in	74.4		
Wheelbase, in	84.6		
Height to top, in	104.4		
Total weight without ballast, lbs	6,620 6,669		
TIRE SIZE			
Front	11.2 - 24		
Rear	16.9 - 30		
Note Specifications and design are subject to	o change without prior notice.		

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Power & tilt steering
- Switch operated Independent PTO
- Front loader valve and 3rd function joystick
- Deluxe adjustable seat
- Remote control valves (3 pair)
- Rear work light
- Horn
- Deluxe cab with AC and heat Cabin air recirculation
- Front & rear windshield washer/wipers
- · Deluxe stereo system with CD player

- 7 pin electrical connector Draw bar
- · Hydraulic draft & position control with auto lift Pre-heat starting aid
- Hand & foot accelerator control
- Safety flashers & turn signals
- · Fuel, coolant temperature, tachometer & hour meter gauges
- Differential lock, parking brake, battery charging, engine oil
- pressure, fuel filter, hydraulic oil filter pressure, 4WD, PTO
- operation, high beam operation / warning lights



Dealer Imprint Zone

LL6100

MT5 Series

78 126.5

95.3 5.7

64 38

7.0

64.2

3,626

6.644

1,232





- Eco-Friendly Tier4 Engine
- 6 year warranty*
- 20x20 Fully Synchronized Shuttle Shift or 20x20 power shuttle
- Wide & Clear View cab
- 3 Pairs of Front Outlet Valves with 3rd Function Joystick
- 3 sets of remote (2 remote valves with float & detent functions)
- Creeper Gear
- grill guard

39000956 - 1706

MT5 Series MT573C/MT573CPS **Utility Tractors**

• Available quick attach, self-leveling front end loader with skid steer compatible bucket &

* 6-year limited warranty. See dealer for details.

MT5 Series Utility Tractors







Clear view cabin

The spacious cabin offers a clear 360° view of the full working width of attached implements



The hood design combined with a large windshield and the sunroof provide a clear view with minimal obstructions.



Power shuttle Easily change from forward or reverse with a simple flick of a lever without depressing the clutch pedal.





Outstanding lift capacity An external secondary hydraulic cylinder provides superior lift capacity(6,614 lbs) to handle a wide range of implements



Hand clutch The hand clutch button added to the gear control lever enables you to change gears easily.



3 pairs of front outlet valves and 3rd function joystick 3 pairs of front outlet valves and joystick with easy-to-control buttons.



The air suspension seat with 10 degree swivel for added comfort.



Newly designed headlamps The high-output projection lamp lights up even the darkest of nights.

Excel in Your Field



Standard creeper Ultra-slow 0.12mph operation provides increased versatility without the additional cost.