

Excel in Your Field™

Specifications

CATEGORY	MT345E	MT345EH	MT350E	MT350EH
ENGINE				
Type	3 – CYL. Turbo, CRDI, Water-cooled			
Model	L3C19-T			
Emission	EPA & CARB Tier4, EC Stage III B			
Engine HP (kW)	45 (33.5)	45 (33.5)	50 (37.3)	50 (37.3)
PTO HP	38.2	36.0	42.5	40.0
Rated speed, rpm.	2,600			
Displacement-cu, in³.	114.7			
Fuel tank capacity, gal.	13.7			
DRIVE TRAIN				
Transmission	Synchro Shuttle / Constant mesh	HST	Synchro Shuttle / Constant mesh	HST
No. of Speed	F8 × R8	3 Ranges	F8 × R8	3 Ranges
Brakes	Wet, Multi-disc			
PTO				
Type	Independent			
Rear, rpm.	540			
HYDRAULIC SYSTEM				
Control system	Position			
Implement pump, gpm.	8.2			
Steering pump, gpm.	4.1			
Total flow, gpm.	12.3			
Category, 3pt hitch.	CAT I			
Hitch lift capacity, lbs (Hitch end)	2,910			
Remote valves	1 or 2 pairs (Option)			
Steering	Hydrostatic Power Steering			
DIMENSION				
Overall length, Bumper to link in.	125			
Overall width with tires, in.	68			
Wheelbase, in.	74.8			
Height to top of rops, in.	98.7			
TIRE SIZE				
Industrial (Front/Rear)	10.0-16.5 / 17.5L-24			
Ag (Front/Rear)	9.5-16 / 14.9-24			
Turf tire (Front/Rear)	29x12.50-15 / 44x1.00-20			
WEIGHT				
Total weight without ballast, lbs.	3,724	3,750	3,724	3,750

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Dry-type air cleaner
 - Pre-heat starting aid
 - Hand and foot throttle control
 - Warning and engine oil pressure light
 - Hydrostatic power steering
 - Front loader valve and joystick
 - Adjustable Seat with seat belt
- Drawbar
 - Turn signals
 - Safety flashers
 - Foldable ROPS
 - Telescopic stabilizer



LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC
P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

ROCKIN' MOOSE
LS
(956) 318-1370 • (956) 605-0051
info@rockinmoose.com

3901 W. Hwy 107 - McAllen, TX 78501



MT3E Series

MT345E / MT345EH / MT350E / MT350EH
Value Compacts



Excel in Your Field™

- Eco friendly Tier4 45HP and 50HP engines
- 6 year warranty*
- F/R Synchronized shuttle or 3 ranges HST with Cruise control
- Front wheel mechanical assist 4WD
- Choice of ag, industrial or turf tires at no additional cost
- Available quick attach front end loader
- Available sub frame mounted, 7’ Backhoe


*6-year limited warranty. See dealer for details

MT3E Series Value Compacts

Excel in Your Field™




Fender mounted joystick for front end loader
Easily accessible for maximum comfort and convenience.




Dual pedal, 3 range HST (HST model)
Easier and more comfortable than rocker pedals. Includes cruise control.



Independent PTO switch
Turn the independent PTO on or off with a simple switch.



New LS Tier4 CRDI engine 45/50hp
LS Tier4 engine meets EPA's most stringent emission standards while delivering rated horse power quietly with a low vibration.



Large fuel tank (13.7 gallon)
The fuel tank provides long operation times between fill-ups.



Your choice of tires
Choose ag, industrial or turf tires at no additional cost.



3-point hitch
Category 1 with a hitch lift capacity of 2,910 lbs allows usage of wide variety of implements.



Comfortable seat (slope type)
The high-quality ergonomically designed seat enhances comfort to reduce fatigue.



Ergonomically designed gear lever
Optimized location of levers maximizes space and helps the operator to control the machine easily.