## Excel in Your Field

### **Specifications**

CATEGORY	XU6158	XU6158C	XU6168	XU6168C	XU6168CPS	Front end Loader
ENGINE						Tractor Applicatio
Туре	4Cyl. In-line Vertical, Water-cooled 4cycle Turbo Diesel, CRDI					Bucket Size, in.
Model(Tier4)			L4C25-T			Maximum Lift Heigh
Engine HP(Gross)	5	8		68		Clearance with Atta
PTO HP	51	.2		60		Reach at Maximum
Rated speed, rpm			2,500			Maximum Dump Ar
Displacement-cu, in <sup>3</sup> .			152.8			Maximum Rollback
Fuel tank capacity, gal			15.8/21.1			Digging Depth, in.
Alternator(V-A)			12-70			Overall Height in Ca
DRIVE TRAIN						Lift Capacity(@ Pivo
Transmission		Synch	ro Shuttle / Powe	r Shuttle		Breakout Force(@ F
No. of Speed			F16 x R16			
Brakes			Wet, Multi - disc			Backhoe
Steering		Hydi	rostatic Power St	eering		Tractor Application
РТО						Digging Depth, in.
Туре			Independent			Reach from centerl
Rear, rpm			540			Loading Height, in.
HYDRAULIC SYSTEM						Swing Arc, deg.
Control system			Position / Draft			Transport Height, ir
Implement pump, gpm			9.9			Bucket Rotating, d
Steering pump, gpm			4.6			Stabilizer Spread(D
Total flow, gpm			14.5			Stabilizer Spread(U
Category, 3pt hitch			CAT II			Bucket Digging for
Hitch Lift capacity, lbs(Hitch end)			4,079			
Remote valves			2 pairs			Additional Equi
DIMENSION						Deluxe cabin with
Overall length, Bumper to link in.			138.6			<ul> <li>Cabin air recircula</li> <li>Front &amp; rear winds</li> </ul>
Overall width with tires, in.			70			Deluxe stereo syst
Wheelbase, in.			80.3			
Ht to top of rops, in.	103	100.6	103	10	00.6	Dealer Installed
TIRE SIZE						<ul> <li>Beacon lamp kit</li> </ul>
Ag Front / Rear		(	9.5 - 20 / 16.9 - 2	24		
IND Front / Rear	10.5 / 80 - 18, 19.5L - 24					
Turf Front / Rear	36 x 13.5 - 15, 16.9 - 24					
WEIGHT			,			
Total weight without ballast, lbs.	4,674	5,121	4,674	5,	121	
Note Specifications and design are sul	biect to change w	ithout prior potice		,		

Front end Loader	LL5106
Tractor Application	XU6100 Series
Bucket Size, in.	72
Maximum Lift Heigh, in.	116.3
Clearance with Attachment Dump, in.	82.8
Reach at Maximum Height, in.	6.6
Maximum Dump Angle, deg.	72
Maximum Rollback Angle, deg.	46
Digging Depth, in.	4.2
Overall Height in Carry Position, in.	68.9
Lift Capacity(@ Pivot pin), lbs.	2,981
Breakout Force(@ Pivot pin), lbs.	4,767

Backhoe	LB3102
Tractor Application	XU6100 Series
Digging Depth, in.	94.5
Reach from centerline of swing Pivot, in.	136.2
Loading Height, in.	80.3
Swing Arc, deg.	180
Transport Height, in.	92.9
Bucket Rotating, deg.	180
Stabilizer Spread(Down position), in.	68.7
Stabilizer Spread(Up position), in.	46.5
Bucket Digging force, lbs.	3,740

#### ipment on Cab Models

h Heating and A/C lation shield washer/wiper system stem with CD Player, USB

#### d Options

Note Specifications and design are subject to change without prior notice.

#### **Get More Standard Features**

- Dry-type air cleaner
- Pre-heat starting aid
- Hand and foot throttle control
- Instrumentation-alternator
- Warning and engine oil pressure light
- Remote control vales (2 pairs) Hydrostatic power & tilt steering
- Front loader valve and joystick
- Hydraulic draft and position control Automatic lift Adjustable seat • Extendable lower links and telescopic stabilizers Drawbar Turn signals
- Safety flashers
- Standard 7 pin implement socket





P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

(956) 318-1370 • (956) 605-0051 info@rockinmoose.com **3901 W. Hwy 107 - McAllen, TX** -1801

ROCKIN' MOOSE LS







- Eco-friendly TIER 4 58HP and 68HP engines
- 5 year warranty\*
- 16F x 16R fully synchronized shuttle shift or power shift (XU6168CPS model) • Front wheel mechanical assist 4WD
- Choice of industrial, ag or turf tires at no additional cost
- Available with quick attach skid steer compatible front end loader with grill guard
- Available sub frame mounted, quick attach 8' backhoe

## **XU6100 Series** XU6158 / XU6158C / XU6168 / XU6168C / XU6168CPS Utility Tractors

# **Excel in Your Field**<sup>™</sup>

## XU6100 Series Utility Tractors





2 sets of remotes and detent function standard

Adds functionality and improves ease of use by allowing attachment of hydraulically controlled implements without the high, additional costs to add the remotes as options



SKC bucket, self leveling front end loader with skid steer compatible bucket Easy to take off or attach loader and easily change loader attachments. With up to 2,981

change loader attachments. With up to 2,981 lbs of lift capacity, it outperforms others in its class. Grill guard comes standard with loader rather than an option







New LS Tier 4 CRDI Engine Meets EPA's most stringent emission standards while delivering rated horsepower quietly with low vibration



Power shuttle models Maximizes ease of use with effortless, clutchless directional changes with 16 forward/16 reverse speeds



Flat platform

With rubber mat and side mounted gear lever, maximizes space, improves operator comfort, and makes getting on/off tractor easier



Full function dash panel Important functional data is available at glance for optimum performance and control



Rear work lights Never be in the dark with this hands-free functional feature that allows light to be directed where you need it

## Excel in Your Field



Your choice of tires Choose ag, industrial or turf at no additional cost