

Specifications

CATEGORY	MT230E	MT235E	MT235HE	MT240E	MT240HE
ENGINE					
Type	3Cylinder, liquid-cooled, Diesel, NA, CRDI			3Cylinder, liquid-cooled, Diesel, TC, CRDI	
Model(Tier4)	L3C19-D3	L3C19-D2		L3C19-T4	
Engine HP(Gross)	30	35		40	
PTO HP	25.5	29.7	28	34	32
Rated speed, rpm	2,600				
Displacement-cu, in³.	114.7				
Fuel tank capacity, gal.	7.4				
Alternator(V-A)	12 - 70				
DRIVE TRAIN					
Transmission	Synchro Shuttle	Synchro Shuttle	HST	Synchro Shuttle	HST
No. of Speed	F12 x R12	F12 x R12	3 Ranges	F12 x R12	3 Ranges
Brakes	Wet, Multi - disc				
Steering	Hydrostatic Power Steering				
PTO					
Type	Independent				
Rear, rpm	540 (Standard)				
Mid., rpm	2,000 (Option)				
HYDRAULIC SYSTEM					
Control system	Position				
Implement pump, gpm	8.2				
Steering pump, gpm	4.1	4.1	5.5	4.1	5.5
Total flow, gpm	12.3	12.3	13.7	12.3	13.7
Category, 3pt hitch	CAT I				
Hitch Lift capacity, lbs(Hitch end)	1,808				
Remote valves	Option				
DIMENSION					
Overall length, Frame to link, in.	121				
Overall width with tires, in.	54				
Wheelbase, in.	69				
Ht to top of rops, in.	88				
TIRE SIZE					
Ag Front / Rear	7 - 14 / 11.2 - 24				
IND Front / Rear	25x 8.5 - 14 / 43x16 - 20				
Turf Front / Rear	25x 8.5 - 14 / 41x14 - 20				
WEIGHT					
Total weight without ballast, lbs.	2,866	2,866	2,870	2,881	2,884

Note Specifications and design are subject to change without prior notice.

Get More Standard Features

- Power steering
 - Switch operated Independent rear PTO
 - Foldable ROPS with seat belt
 - Hydraulic position control
 - Differential lock
 - Draw bar
 - Pre-heat starting aid
- Rubber floor mat and secure fender grip
 - Convenient cup holder and toolbox
 - Safety flashers
 - Fuel, coolant temperature, tachometer & hour meter gauges
 - Pre-heating, parking brake, battery charging, engine oil pressure, fuel filter, PTO operation and high beam operation/warning lights



LS Tractor USA | 6900 Corporation Parkway, Battleboro, NC
P: 252.984.0700 | F: 252.984.0701 | www.lstractorusa.com

Front end Loader	LL3301	LL3302
Tractor Application	MT230E / MT235E / MT235HE	MT240E / MT240HE
Bucket, in.	66	
Maximum Lift height, in.	94	
Clearance with Attachment Dump, in.	65.6	
Reach at Maximum Height, in.	11.5	
Maximum Dump Angle, deg.	57	
Maximum Rollback Angle, deg.	40	
Digging Depth, in.	5.5	
Overall Height in Carry Position, in.	53	
Lift Capacity(@ Pivot pin), lbs.	1,688	2,153
Breakout Force(@ Pivot pin), lbs.	2,855	3,579
Approx. Weight (Loader w/o Bucket), lbs.	650	653

Backhoe	LB1105
Tractor Application	MT230E / MT235E / MT235HE / MT240E / MT240HE
Digging Depth, in.	76.3
Reach from centerline of swing Pivot, in.	113.1
Loading Height, in.	63.6
Swing Arc, deg.	180
Transport Height, in.	77.2
Bucket Rotating, deg.	180
Stabilizer Spread(Down position), in.	68.7
Stabilizer Spread(Up position), in.	46.4
Bucket Digging force, lbs.	2,817

Snow Blower	LW3163B	LW3174B
Tractor Application	All MT2E Series	MT240E / MT240HE
Overall width, in	68	74
Cutting width, in	63, (68 with extension)	74
Cutting height, in	23	26
Impeller drive	Gear box	
Auger drive	Worm gear	Chain drive
Auger diameter, in	13 3/4	14 3/4
Impeller diameter, in	17 5/8	23 3/4
Number of blades on impeller	4	
Chute rotation	Hydraulic	
Adjustable heavy skid shoes	Yes	



Dealer Imprint Zone

39000958-1906



MT2E Series

MT230E / MT235E / MT235HE / MT240E / MT240HE
Value Compacts



- 30HP, 35HP & 40HP, 3 cylinder fuel efficient engine
- 6 year warranty*
- 12x12 synchro shuttle or 3 range HST with cruise control
- Front wheel mechanical assist 4WD
- Flat operator platform
- Choice of industrial, ag or turf tires at no additional cost
- Available quick attach front end loader with skid steer compatible bucket & grill guard
- Available sub-frame mounted, quick attach 6’ backhoe
- Optional mid-mount PTO

*6-year limited warranty. See dealer for details

MT2E Series Value Compacts



Hydrostatic transmission models
Maximizes ease of use with effortless, clutch-less and instant speed and directional changes with a simple push of the pedal



SKC bucket, front end loader with skid steer compatible bucket
Easy to take off or attach loader and easily change loader attachments. With up to 2,153 lbs of lift capacity, it outperforms others in its class. Grill guard comes standard with loader rather than an option



Your choice of tires
Choose ag, industrial or turf tires at no additional cost



New LS Tier 4 CRDI Engine
Meets EPA's most stringent emission standards while delivering rated horsepower quietly with low vibration



Full function dash panel
Important functional data is available at glance for optimum performance and control



Easy open one-piece hood
Provides accessibility for easy maintenance



Tilt steering wheel
Convenient lever allows you to adjust the tilt for maximum comfort



PTO On/Off switch
Best easy and safety Independent PTO control with electric on/off switch. User friendly design and location for simple PTO operation.



Adjustable seat, firm fender grip, and cup holder
Offers comfort and convenience even during long operations.