

LS Tractor



MT2S SERIES

MT225s

PREMIUM COMPACT TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT2S SERIES

PREMIUM COMPACT TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



BACKHOE:
Excellent Capacity,
Smooth And
Consistent Operation
For Added Control



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- **6 Year Warranty***
- **24.7 HP Yanmar Diesel Engine**
- **3 Range Hydrostatic Transmission (2 Pedal)**
- **Electric Engagement Independent PTO**
- **New Heavy-Duty Platform/Frame**



Premium Reversible Seat
Adjustable Foldable
Armrest, Tilt High Back Seat.
*Reversible Seat Only On
Backhoe Models



**3 Range Hydrostatic
Transmission**
(2 Pedal) Comfortable And
Efficient Operator Control



Bolted Edge Bucket
Built For The
Harshest Conditions



**Standard Factory Grille
Guard W/ Loader**
Full Length Grille Guard
Protect Body Panels
And Radiator



**Optional Thumb
Configuration Backhoe**
Provides Added Functionality
To The Heavy-Duty Backhoe



**Optional Drive-Over
Mid-Mount Mower Deck**
Providing Convenience And
Ease Of Adapting To Any
Application



Standard Tilt Steering
Provides Enhanced
Operator Comfort



Standard Foldable ROPS
Enables Easy Adjustment
For Clearance



**Mid-Mount Mower
Height Adjustment Dial**
Enables Precise Height
Control Of The Mid-Mount
Mower, By A Simple Turn

MT225s



SPECIFICATIONS

CATEGORY	
ENGINE	MT225s
Type	3 Cylinder-IDI
Model (Tier 4)	3TNV80F-ZXKLST (Yanmar)
Engine HP (gross)	24.7
PTO (HP)	19.3
Rated Speed (rpm)	2,800
Displacement-cu (in ³ .)	77.3
Fuel Tank Capacity (gal.)	6.79
Alternator (V-A)	12 - 40
DRIVE TRAIN	
Transmission	HST
No. Of Speed	3 Ranges
Brakes	Wet, Multi-disc
PTO	
Type	Independent
Rear (rpm)	540
Mid PTO (Option)	2,500
HYDRAULIC SYSTEM	
Lift Control System	Position
Implement Pump (gpm)	5.6
Steering Pump (gpm)	3.7
Steering	Hydrostatic Power Steering
Total Flow (gpm)	9.3
Category (3pt Hitch)	CAT I
Hitch Lift Capacity (lbs.) (Hitch End)	1,896
Remote Valves	1 Pair (Option)
DIMENSION (with R1 tires)	
Overall Length (Frame To Link in.)	111.9
Overall Width With Tires (in.)	48.7
Wheelbase (in.)	63.4
Height To Top Of ROPS (in.)	86.4
TIRE SIZE	
Front / Rear Ag (R1)	7 - 12 / 11.2 - 16
Front / Rear Industrial (R4)	23 x 8.5 - 12 / 12 - 16.5
Front / Rear Turf (R3)	22 x 8.5 - 12 / 31 x 15.5 - 15
WEIGHT	
Total Weight w/o Ballast (lbs.)	1,764

Note specifications and design are subject to change without prior notice.

FRONT END LOADER	
TRACTOR APPLICATION	LL2300
Bucket Size (in.)	54.3
Maximum Lift Height (in.)	84.4
Clearance With Attachment Dump (in.)	59.1
Reach At Maximum Height (in.)	17.9
Maximum Dump Angle (deg.)	55
Maximum Rollback Angle (deg.)	40
Digging Depth (in.)	4.5
Overall Heights In Carry Position (in.)	46
Lift Capacity (At Pivot Pin) (lbs.)	1,067
Breakout Force (At Pivot Pin) (lbs.)	2,290
Approx. Weight (Loader w/o Bucket) (lbs.)	708

BACKHOE	
TRACTOR APPLICATION	LB1300
Digging Depth (in.)	84.9
Reach From Centerline Of Swing Pivot (in.)	113.7
Loading Height (in.)	64.7
Swing Arc (deg.)	180
Transport Height (in.)	73.4
Bucket Rotating (deg.)	177
Stabilizer Spread (Down Position) (in.)	82.2
Stabilizer Spread (Up Position) (in.)	65.4
Bucket Digging Force (lbs.)	3,013

MID MOWER	
TRACTOR APPLICATION	LM2360
Cutting Width (in.)	60
Cutting Height Range (in.)	1 - 4
Transport Height (in.)	6
Gear Type	Spiral Bevel
Number Of Blades	3
Adjustment Of Cutting Height	Dial
Deck Thickness (in.)	0.15
Total Width (in.)	75.7
Total Length (w/o Linkage)	44.1
Total Height (w/o Linkage)	11.9
Lifting Type	3-Point Upper Link
Total Weight (lbs.)	368

Additional Equipment

- Standard Factory Toolbox
- Standard 12 Volt Power Outlet
- Flat Operator With Rubber Mat
- Standard Factory Platform Step



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

