

MT4 SERIES

LS Tractor



MT458 / MT458CPS / MT468 / MT468C / MT468CPS
PREMIUM UTILITY TRACTORS

6-YEAR LIMITED WARRANTY. SEE DEALER FOR DETAILS

MT4 SERIES

PREMIUM UTILITY TRACTORS

RECOMMENDED IMPLEMENTS/ ATTACHMENTS



LOADER:
High Capacity With
An Abundance Of
Standard Features



LAND GRADER:
Heavy Steel
Construction, High
Strength, Designed
For Use In Demanding
Applications



ROTARY CUTTER:
Durable Heavy Steel
Design Providing
Quality And Strength



BOX BLADE:
Features A Heavy
Welded Steel
Design For Use In
Demanding Applications

FEATURES

- **6 Year Warranty***
- **16F x 16R Fully Synchronized Shuttle Shift or 16F x 16R Power Shuttle Shift (CPS Models) Transmission**
- **Backhoe Compatible**
- **Premium Ergonomically Designed Cab**
- **Standard High Capacity Three-Point And Loader Lift Capacity**



**Available With Three
Rear Remotes (Cab Only)**
Provides Added Flexibility
For Attachments And
Implements



**Standard Ground Control
Three-Point Adjustment**
Provides Ground Controllability
Of Three-Point Position To
Enable Easier Connectivity
With Implements



**Standard Right-Side Cab
Door With Steps**
Provides Additional Access
To The Operators Platform



**Standard Telescopic
Link Arms**
Enables Connecting
Three-Point Implements
Easier



Standard Drawbar
Added Value Of Providing
Essential Heavy-Duty
Features



**Standard Grille Guard With
Loader And Position ROD**
Protects Grille And Radiator
In Loader Applications



**Standard Large
Adjustable Mirrors**
Provide Visibility In A
Variety Of Applications



Ground Level Fuel Tank
Provides Easier Fueling
Access



**Variety Of Tires To Choose,
Including Titan Tires**
Provides A Variety Of Tread
Patterns And Sizes To Accommodate
Customer Applications

MT458 / MT458CPS / MT468 / MT468C / MT468CPS



SPECIFICATIONS

CATEGORY	MT458	MT458CPS	MT468	MT468C	MT468CPS
ENGINE	MT458	MT458CPS	MT468	MT468C	MT468CPS
Type	4Cylinder In-line Vertical, Water-cooled 4cycle Turbo Diesel, CRDI				
Model (Tier 4)	L4C25-T				
Engine HP (gross)	58			68	
PTO (HP)	51.2			60	
Rated Speed (rpm)	2,500				
Displacement (in ³)	152.8				
Fuel Tank Capacity (gal.)	21.1				
Alternator (V-A)	12-70				
DRIVE TRAIN	Synchro Shuttle / Power Shuttle (CPS Models)				
Transmission	Synchro Shuttle / Power Shuttle (CPS Models)				
No. Of Speed	F16 x R16				
Brakes	Wet, Multi-disc				
PTO	Independent				
Type	Independent				
Rear (rpm)	540				
HYDRAULIC SYSTEM	Position / Draft				
Control System	Position / Draft				
Implement Pump (gpm)	9.9				
Steering Pump (gpm)	4.6				
Steering	Hydrostatic Power Steering				
Total Flow (gpm)	14.5				
Category (3pt Hitch)	CAT II				
Hitch Lift Capacity (Hitch End) (lbs.)	4,079				
Remote Valves	2 Pairs Standard				
DIMENSION	138.6				
Overall Length (Bumper To Link in.)	138.6				
Overall Width With Tires (in.)	70				
Wheelbase (in.)	80.3				
Height To Top Of ROPS (in.)	103	100.6	103		100.6
TIRE SIZE	9.5 - 20 / 16.9 - 24				
Front / Rear Ag	9.5 - 20 / 16.9 - 24				
Front / Rear Industrial	10.5 / 80 - 18, 19.5L - 24				
Front / Rear Turf	36 x 13.5 - 15, 16.9 - 24				
WEIGHT	4,674				
Total Weight w/o Ballast (lbs.)	4,674	5,121	4,674		5,121

FRONT END LOADER	LL5106
TRACTOR APPLICATION	MT4 SERIES
Bucket Size (in.)	72
Maximum Lift Height (in.)	116.3
Clearance With Attachment Dump (in.)	82.8
Reach At Maximum Height (in.)	6.6
Maximum Dump Angle (deg.)	72
Maximum Rollback Angle (deg.)	46
Digging Depth (in.)	4.2
Overall Height In Carry Position (in.)	68.9
Lift Capacity (At Pivot Pin) (lbs.)	2,981
Breakout Force (At Pivot Pin) (lbs.)	4,767

BACKHOE	LB3102
TRACTOR APPLICATION	MT4 SERIES
Digging Depth (in.)	94.5
Reach From Centerline Of Swing Pivot (in.)	136.2
Loading Height (in.)	80.3
Swing Arc (deg.)	180
Transport Height (in.)	92.9
Bucket Rotating (deg.)	180
Stabilizer Spread (Down Position) (in.)	68.7
Stabilizer Spread (Up Position) (in.)	46.5
Bucket Digging Force (lbs.)	3,740

Additional Equipment Available

- Deluxe Cabin With Heating & A/C
- Cabin Air Recirculation
- Front & Rear Windshield Washer/Wiper System (Cab Only)
- Deluxe Stereo System With CD Player, USB (Cab Only)
- Pre-heat Starting Aid
- Hand & Foot Throttle Control
- Tilt Steering
- Front Loader Valve And Joystick
- Hydraulic Draft & Position Control
- Adjustable Seat
- Lower Links & Telescopic Stabilizers
- Drawbar
- Flashers
- 7-Pin Implement Socket

**All Specs and features are subject to change, and pictures could include optional equipment etc.*



LS Tractor

LS Tractor USA | P: 252.984.0700 | F: 252.984.0701 | LSTractorUSA.com
(Corporate Address) 6900 Corporation Parkway, Battleboro, NC

